

KOMATSU

PC130LC-11

Tier 4 final engine



General machine information

Net horsepower	97.2 HP @ 2,050 rpm	72.5 kW @ 2,050 rpm
Operating weight	28,440 lb - 29,101 lb	12,900 kg - 13,200 kg
Bucket capacity	0.34 - 0.78 yd ³	0.26 - 0.60 m ³

Features and benefits

A powerful Komatsu SAA4D95LE-7 engine provides a net output of 72.5 kW 97.2 HP. This engine is EPA Tier 4 Final emissions certified.

New longer undercarriage design increases track length by 8%, improving lifting capacity by 20% versus the previous model. This new design also increases stability and can help to boost overall productivity.

Variable flow turbocharger improves engine response and provides optimum air flow under all speed and load conditions.

Komatsu diesel oxidation catalyst (KDOC) reduces particulate matter using passive regeneration over 98% of the time.

Selective catalytic reduction (SCR) reduces NOx and has easy to access components.

Komatsu auto idle shutdown helps reduce nonproductive engine idle time and reduces operating costs.

Komatsu's closed-center load sensing system (CLSS) provides quick response and smooth operation to help maximize productivity.

Enhanced working modes are designed to match engine speed, pump delivery, and system pressure to the application.

Temperature-controlled fan clutch helps improve fuel efficiency and lower sound levels.

Large LCD color monitor panel:

- 7" high resolution screen
- Provides guidance for fuel-efficient operation
- Enhanced attachment control

Aux jack and one 12V outlet for audio devices and accessories. Bluetooth radio functionality included.

Rearview monitoring system (standard) promotes zero harm.

Equipment management monitoring system (EMMS) continuously monitors machine operation and vital systems to identify machine issues and assist with troubleshooting.

Enhanced working environment

- Integrated ROPS cab design (ISO 12117-2)
- Cab meets ISO Level 1 Operator Protective Guard (OPG) top guard (ISO 10262)

High performance in a lightweight package

A powerful engine and heavy-duty work equipment provide exceptional performance in an easy to transport package. A conventional cab provides a quiet, comfortable, and spacious work environment.

Wide access service doors provide easy access for ground level maintenance.

Komatsu designed and manufactured components are engineered for performance and reliability.

New engine and hydraulic control technology improves operational efficiency and lowers fuel consumption by up to 12% compared to the previous generation.

New quick return arm valve improves arm cylinder hydraulic flow for faster arm out speed and performance.

Handrails (standard) provides convenient access to the upper structure.

Battery disconnect switch allows a technician to disconnect the powersupply before servicing the machine.

The Komtrax[®] telematics system is standard on Komatsu equipment with no subscription fees throughout the life of the machine. Using the latest wireless technology, Komtrax transmits valuable information such as location, utilization, and maintenance records to a PC or smartphone app. Custom machine reports are provided for identifying machine efficiency and operating trends. Komtrax also provides advanced machine troubleshooting capabilities by continuously monitoring machine health.



Specifications

Engine

Model	Komatsu SAA4D95LE-7*	
Type	Water-cooled, 4-cycle, direct injection	
Aspiration	Variable flow, turbocharged, air-to-air aftercooled	
Number of cylinders	4	
Bore	95 mm	3.74"
Stroke	115 mm	4.53"
Piston displacement	3.26 L	199 in ³
Horsepower		
SAE J1995 (gross)	72.6 kW	97.3 HP
ISO 9249/SAE J1349 (net)	72.5 kW	97.2 HP
Rated rpm	2,050 rpm	
Fan at maximum speed (net)	67.8 kW	90.9 HP
Fan drive method for radiator cooling	Mechanical with viscous clutch	
Governor	All-speed control, electronic	

*U.S. EPA Tier 4 final emission certified

Hydraulics

Type	HydrauMind (Hydraulic Mechanical Intelligence) system, closed-center system with load sensing valve and pressure compensated valve	
Number of selectable working modes	6	
Main pump		
Type	Variable capacity piston type	
Pump for	Boom, arm, bucket, swing, and travel circuits	
Maximum flow	242 ltr/min	64 gal/min
Hydraulic motors		
Travel	2 x piston motor with parking brake	
Swing	1 x piston motor with swing holding brake	
Relief valve setting		
Implement circuits	34.8 MPa	355 kgf/cm ² 5,050 psi
Travel circuit	34.8 MPa	355 kgf/cm ² 5,050 psi
Swing circuit	39.2 MPa	298 kgf/cm ² 4,240 psi
Pilot circuit	3.2 MPa	33 kgf/cm ² 470 psi
Maximum Auxiliary Flow (at 250 kgf/cm ² 3,553 psi)*	242 ltr/min	64 gal/min
Number of hydraulic cylinders – bore x stroke x rod diameter	115 mm	4.53"
Boom (2)	105 mm x 995 mm x 70 mm	4" x 39" x 3"
Arm (1)	115 mm x 1,175 mm x 75 mm	5" x 46" x 3"
Bucket (1)	95 mm x 885 mm x 65 mm	4" x 35" x 3"

*Auxiliary flow is adjustable through the monitor

Drive and brakes

Steering control	HydrauMind (Hydraulic Mechanical Intelligence) system, closed-center system with load sensing valve and pressure compensated valve	
Drive method	Fully hydrostatic	
Maximum drawbar pull	123 kN	12,500 kgf 27,560 lbf
Gradeability	70%, 35°	
Maximum travel speed (auto-shift)	Boom, arm, bucket, swing, and travel circuits	
High	5.5 kph	3.4 mph
Low	2.9 kph	1.8 mph
Service brake	Hydraulic lock	
Parking brake	Wet, multiple-disc	

Swing system

Driven by	Hydraulic motor	
Swing reduction	Planetary gear	
Swing circle lubrication	Grease-bathed	
Service brake	Hydraulic lock	
Swing lock	Wet, multiple-disc brake	
Swing speed	11.0 rpm	
Swing torque	2,991 kg-m	21,627 ft.-lbs.

Undercarriage

Driven by	X-frame leg	
Track frame	Box-section	
Track type	Sealed track	
Track adjuster	Hydraulic	
Number of shoes (each side)	46	
Number of carrier rollers (each side)	2	
Number of track rollers (each side)	8	

Sound Performance

Exterior – ISO 6395	101 dB(A)
Operator – ISO 6396	71 dB(A)

Coolant & lubricant capacity (refilling)

Fuel tank	250 L	66 US gal
Coolant	17.7 L	4.6 US gal
Engine	11.5 L	3.0 US gal
Final drive, each side	2.1 L	.55 US gal
Swing drive	2.5 L	.7 US gal
Hydraulic tank	69.0 L	18.2 US gal
DEF tank	21.1 L	5.6 US gal

Operating weight (approximate)


Operating weight includes 4 600 mm 15'1" one-piece boom, 2 500 mm 8'2" arm, SAE heaped 0.51 m³ 0.67 yd³ backhoe bucket, rated capacity of lubricants, coolant, full fuel tank, operator, and standard equipment

Grouser	Operating weight	Ground pressure ISO16754
500 mm, 20" Road liner	12,900 kg 28,440 lb	37.3 kPa / 0.38 kg/cm ² 5.40 psi
600 mm, 24" Triple	13,000 kg 28,660 lb	31.3 kPa / 0.32 kg/cm ² 4.54 psi
700 mm, 28" Triple	13,200 kg 29,101 lb	27.2 kPa / 0.28 kg/cm ² 3.95 psi

Component weights

Arm, including bucket cylinder and linkage		
2500 mm 8'2" arm assembly	529 kg	1,164 lb
2500 mm 8'2" arm assembly w/piping	558 kg	1,228 lb
One piece boom including arm cylinder		
4600 mm 15'1" boom	809 kg	1,783 lb
Counterweight	1,850 kg	4,078 lb
Bucket (0.51 m ³ 0.67 yd ³ 762 mm 30" width)	517 kg	1,140 lb

Lift capacities with lifting mode



- A: Reach from swing center
- B: Bucket hook height
- C: Lifting capacity
- Cf: Rating over front
- Cs: Rating over side
- ⊗: Rating at maximum reach

- Conditions:**
- 4600 mm 15' 1" one-piece boom
 - Counterweight (total mass): 1,850 kg / 4,070 lb
 - Bucket: none
 - Lifting mode: on

Specification: 4,600 mm boom, 2,500 mm arm, bucketless (no bucket link, no bucket cylinder), no ATT piping, 500 mm shoe (road liner) Unit: lb kg

B	A		MAX		25' 7.6 m		20' 6.1 m		15' 4.6 m		10' 3.0 m		5' 1.5 m	
	MAX	MAX	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs
20' 6.1 m	18' 5.6 m	* 5,320 2,410	* 5,320 2,410					* 7,560 3,420	* 7,560 3,420					
15' 4.6 m	22' 6.6 m	* 4,990 2,260	4,640 2,100			* 7,900 3,580	5,280 2,390	* 7,920 3,590	* 7,920 3,590					
10' 3.0 m	23' 7.1 m	* 5,010 2,270	4,050 1,830			8,050 3,650	5,160 2,340	* 9,680 4,390	7,890 3,580	* 12,770 5,790	* 12,770 5,790			
5' 1.5 m	24' 7.3 m	* 5,300 2,400	3,820 1,730			7,820 3,550	4,960 2,250	* 12,000 5,440	7,400 3,350	* 18,300 8,300	* 13,310 6,030			
0' 0 m	23' 7.1 m	* 5,930 2,690	3,870 1,750			7,630 3,460	4,780 2,170	11,690 5,300	7,040 3,190	* 16,140 7,320	12,520 5,680			
-5' -1.5 m	22' 6.6 m	6,750 3,060	4,240 1,920			7,540 3,420	4,700 2,130	11,510 5,220	6,880 3,120	* 20,520 9,300	12,420 5,630	* 9,820 4,450	* 9,820 4,450	
-10' -3.0 m	18' 5.6 m	8,500 3,850	5,270 2,390					11,580 5,250	6,940 3,140	* 17,740 8,040	12,600 5,710	* 21,400 9,700	* 21,400 9,700	
-15' -4.6 m														

Specification: 4,600 mm boom, 2,500 mm arm, bucketless (no bucket link, no bucket cylinder), no ATT piping, 600mm shoe (triple grouser) Unit: lb kg

B	A		MAX		25' 7.6 m		20' 6.1 m		15' 4.6 m		10' 3.0 m		5' 1.5 m	
	MAX	MAX	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs
20' 6.1 m	18' 5.6 m	* 5,340 2,420	* 5,340 2,420					* 7,570 3,430	* 7,570 3,430					
15' 4.6 m	22' 6.6 m	* 5,000 2,260	4,730 2,140			* 7,890 3,580	5,340 2,420	* 7,870 3,570	* 7,870 3,570					
10' 3.0 m	23' 7.1 m	* 5,000 2,270	4,020 1,870			8,160 3,700	5,230 2,370	* 9,590 4,350	8,000 3,630	* 12,480 5,660	* 12,480 5,660			
5' 1.5 m	24' 7.3 m	* 5,280 2,390	3,880 1,760			7,940 3,600	5,030 2,280	* 11,910 5,400	7,510 3,400	* 18,090 8,200	13,520 6,130			
0' 0 m	23' 7.1 m	* 5,890 2,670	3,810 1,770			7,740 3,510	4,850 2,200	11,860 5,380	7,140 3,230	* 16,090 7,290	12,690 5,750			
-5' -1.5 m	22' 6.6 m	6,800 3,080	4,270 1,940			7,640 3,460	4,700 2,160	11,670 5,290	6,970 3,160	* 20,590 9,330	12,570 5,700	* 9,470 4,290	* 9,470 4,290	
-10' -3.0 m	19' 5.7 m	8,500 3,850	5,270 2,390					11,720 5,310	7,020 3,180	* 17,910 8,120	12,750 5,780	* 20,880 9,470	* 20,880 9,470	
-15' -4.6 m										* 11,820 5,360	* 11,820 5,360			

Specification: 4,600 mm boom, 2,500 mm arm, bucketless (no bucket link, no bucket cylinder), no ATT piping, 700mm shoe (triple grouser) Unit: lb kg

B	A		MAX		25' 7.6 m		20' 6.1 m		15' 4.6 m		10' 3.0 m		5' 1.5 m	
	MAX	MAX	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs	Cf	Cs
20' 6.1 m	18' 5.6 m	* 5,340 2,420	* 5,340 2,420					* 7,570 3,430	* 7,570 3,430					
15' 4.6 m	22' 6.6 m	* 5,000 2,260	4,800 2,170			* 7,890 3,580	5,410 2,450	* 7,870 3,570	* 7,870 3,570					
10' 3.0 m	23' 7.1 m	* 5,000 2,270	4,180 1,890			8,270 3,750	5,300 2,400	* 9,590 4,350	8,100 3,670	* 12,480 5,660	* 12,480 5,660			
5' 1.5 m	24' 7.3 m	* 5,280 2,390	3,940 1,780			8,050 3,650	5,100 2,310	* 11,910 5,400	7,610 3,450	* 18,090 8,200	13,700 6,210			
0' 0 m	23' 7.1 m	* 5,890 2,670	3,970 1,800			7,850 3,560	4,920 2,230	12,030 5,450	7,240 3,280	* 16,090 7,290	12,870 5,830			
-5' -1.5 m	22' 6.6 m	6,900 3,130	4,330 1,960			7,760 3,520	4,830 2,190	11,840 5,370	7,070 3,210	* 20,590 9,330	12,750 5,780	* 9,470 4,290	* 9,470 4,290	
-10' -3.0 m	19' 5.7 m	8,620 3,910	5,340 2,420					11,890 5,390	7,120 3,230	* 17,910 8,120	12,920 5,860	* 20,880 9,470	* 20,880 9,470	
-15' -4.6 m										* 11,820 5,360	* 11,820 5,360			

*Asterisk indicates load is limited by hydraulic capacity rather than tipping. Ratings are based on ISO standard No. 10567. Rated load capacity does not exceed 85% of hydraulic lift capacity or 75% of tipping load. Total weight of bucket and/or installed attachments must be deducted from the capabilities shown above. Lift capacity chart is based on machine located on a solid, level and uniform surface. Load ratings are at the arm bucket pin location, use of any attachment point in a different location to handle objects could affect excavator lift performance.

Product designs, specifications and/or data in this document are provided for informational purposes only and are not warranties of any kind. Product designs and/or specifications may be changed at any time without notice. The only warranties that apply to sales of products and services are Komatsu's standard written warranties, which will be furnished upon request.

Komatsu and other trademarks and service marks used herein are the property of Komatsu Ltd. or its subsidiaries, or the respective owners or licensees.

